



Applicable syringe:  
10, 20, 30,  
50/60 ml

Automatic  
Anti-Bolus

Wireless  
Management

# Syringe Pump **OKM SP-600**

# Syringe Pump

OKM SP-600

## Specifications

Model	OKM SP-600
Syringe Size	10, 20, 30, 50/60 ml
Applicable Syringe	Compatible with syringe of any standard
VTBI	0.1-9999 ml <1000 ml in 0.1 ml increments ≥1000 ml in 1 ml increments
Flow Rate	Syringe 10 ml: 0.1-400 ml/h Syringe 20 ml: 0.1-600 ml/h Syringe 30 ml: 0.1-900 ml/h Syringe 50/60 ml: 0.1-1300 ml/h <1000 ml in 0.1 ml increments ≥1000 ml in 1 ml increments
Bolus Rate	Syringe 10 ml: 400 ml/h Syringe 20 ml: 600 ml/h Syringe 30 ml: 900 ml/h Syringe 50/60 ml: 1300 ml/h
Anti-Bolus	Automatic
Accuracy	±2% (mechanical accuracy ≤1%)
Infusion Mode	Flow rate: ml/min, ml/h Time-based Body weight: mg/kg/min, mg/kg/h, ug/kg/min, ug/kg/h, etc.
KVO Rate	0.1-1 ml/h (in 0.1 ml/h increments)
Alarms	Occlusion, near empty, end program, low battery, end battery, AC power off, motor malfunction, system malfunction, reminder alarm, pressure sensor error, syringe installation error, syringe drop off
Additional Features	Real-time infused volume, automatic power switching, automatic syringe identification, mute button, purge, bolus, anti-bolus, system memory
Drug Library	Available
Occlusion Sensitivity	High, medium, low
Power Supply, AC	110/230 V (optional), 50/60 Hz, 20 VA
Battery	9.6±1.6 V, rechargeable
Battery Life	7 hours at 5 ml/h
Working Temperature	5-40°
Relative Humidity	20-90%
Atmospheric Pressure	860-1060 hpa
Size	314*167*140 mm
Weight	2.5 kg
Safety Classification	Class II, type CF



ISO13485:2003



Medical Device G.M.S.  
TS EN ISO13485:2003  
AK-2003/12

OKUMAN Medikal Sistemler Ltd.

Kazım Karabekir Caddesi 95/95  
06060 İskitler  
Ankara / Türkiye

T: +90 312 384 0520  
F: +90 312 384 1975  
info@okuman.com.tr  
www.okuman.com.tr

Catalog ID: .....001-01-2015-EN

© 2015 OKUMAN Medikal Sistemler Ltd. All rights reserved.  
Technical specifications are subject to change by OKUMAN without prior notice.