


| Optional Accessories

Optional accessories for the best way of maximizing the utility of COMFORTCOUGH® II.



| Product information

Specifications

Dimensions (W*H*D)	288mm X 245mm X 212mm	Oscillatory Vibration	Amplitude : 1~10cmH2O / Freq. : 1~20Hz
Weight	4.6kg (without accessories)	Percussor Mode	10~780cpm (Max 13Hz) / +0~70cmH2O
Therapy Features	CoughSync (Flow Trigger)	Oximetry Accessory	SpO2, Heart rate data
Pressure Range	-70 to +70cmH2O	Remote Control	Foot Switch
Inhale Flow	Low, Medium, High	Data Management	SD Card, Comfort Reader
In-Exhalation, Pause Time	0 to 5.0 sec	Power Management	Detachable Battery
Pressure Display	Bar or Graph	Breathing Hose Holder	Included in Main body
Modes of Operation	Auto/Manual/Percussor/No setting	Input Voltage / Power	100-240 VAC, 50/60 Hz, 2A/1A / 120 VA
Preset	9 presets	Electrical Protection	BF, Class II
Degree of Protection against Ingress of Water	IP21		

Order Information

COMFORTCOUGH® II including Device, Detachable Battery, SD Card, Breathing Hose, Face Mask, Bacterial/Viral Filter and Adapter			CC20
Detachable Battery	D60000	Breathing Hose 120cm	38017
Pulse Oximetry Kit		Air Filter	1A6035
Face Mask ; Size 3 ~ 5	5353, 5354, 5355	SD Card	1A6055
Bacterial/Viral Filter	70015	Adapter (Exhalation)	54032
Adapter (Normal)	74505		

* Specification may change without notice

Please contact us for any inquiry!!!

| Website www.comfortcough.com | Phone +82 (2) 325 2106
| Email sungha@seoilpacific.co.kr | Fax +82 (2) 325 2107





Cough Stimulating Device

Innovative Mechanical In-Exsufflator COMFORTCOUGH® II




Maximizing its Efficiency with Outstanding Features

Oscillatory Vibration | Percussor Mode [Intrapulmonary Percussive Ventilation] | High Frequency Chest Wall Vibration | CoughSync [Flow Trigger]




Innovative Features to Maximize Airway Secretion Clearance

Oscillatory Vibration



The oscillatory vibrations assist in loosening and mobilizing the secretions while the rapid shift between positive and negative pressure. The rapid shift produces a high expiratory flow rate from the lungs and promotes the clearance of secretions.

Percussor Mode [Intrapulmonary Percussive Ventilation]



COMFORTCOUGH® II delivers high-frequency ventilation into the lungs, in the form of intrapulmonary percussions. Percussions, ranging from 10 to 780 CPM, consist of small bursts of volume characterized by sharp peaks of pressure. It is expected to loosen and mobilize secretions toward the upper airway of the patient with restrictive and obstructive pulmonary diseases affected by various reasons.

CoughSync [Flow Trigger]



COMFORTCOUGH® II triggers on the patient's inspiratory and expiratory phase to help synchronize the therapy with the patient.

Data Management



Comfort Reader Software and SD Card let the patients, caregivers and respiratory therapists check the data of the therapy at a glance.

High Portability

Compact size and lightweight of COMFORTCOUGH® II offer high portability with the detachable battery and handle.

7 Inches TFT-LCD Display

All information can be checked at a glance with colored and big display. In addition, it is possible to select the type of the pressure display as Bar or Graph for the needs and preferences of patients, caregivers and respiratory therapist.

COMFORTCOUGH® II, the most updated Mechanical In-Exsufflator (MI-E), has been developed to help the patients who cannot clear the bronchopulmonary secretions by oneself due to the various reasons

Compact Size and Light Weight

- High portability with the detachable battery and handle
- Breathing Hose Holder for convenient hose arrangement

First and Foremost Secretion Clearance Device



- Oscillatory vibration effectively enhances mobilization of secretions
- Percussor mode delivers high-frequency ventilation into the lungs in the form of intrapulmonary percussions.
- CoughSync (Flow Trigger) is the most useful function for the patients to adopt COMFORTCOUGH® II.
- 9 preset modes offer various merits to the caregiver.

Data Management

- 8GB SD Card as basic accessory to manage the data efficiently
- Data management system by Comfort Reader Software

7 Inches TFT-LCD Display

- Every information at a glance
- Pressure information as Bar or Graph



Key Pad

- Easy control by pressing the button
- Can be adjusted in increments of 0.1sec and 1cmH2O.



Various Options for Effective Use
Pulse Oximetry Kit | Foot Switch | Stand

Caution! COMFORTCOUGH® II is a medical device and it must only be used under the direction of a physician.